



DOCUMENT N° VDL1/148

© COPYRIGHT VALIANT DESIGNS



Tel: 01-720 3947/627 1351/627 0470 Telex: 946461 (Attn Valiant) NIMTEX G

Directors: Prof T Stonier, AB, MS, PhD, FRSA (President) R R Fawcett, ACMA, MBCS (Chairman)  
D Catlin, B Tech (Managing) G M Manvell (Marketing) T M Airey, BSc, FCA (Finance) (Secretary)

Reg in England No 1626393 Reg Office: 56-60 St Mary Axe, London EC3A 8BJ VAT No 237 711955

POWER ADAPTOR TEST SPECIFICATION: VDL1/148

The following parameters define the output requirements in order to assess the integrity of the power adaptor. It is assumed that the input mains voltage is applied according to its nominal rating.

The output levels should be as follows:

Recommended No Load output nominally 26VDC

Recommended output with 139ohm Load nominally 23VDC<sup>\*</sup>

Recommended output with 39ohm Load nominally 19VDC<sup>\*</sup>

<sup>\*</sup> Notes: A tolerance of  $\pm 0.5V$  is normal, although manufacturing spreads may take this up to  $\pm 1V$ . However, faulty units normally show a gross discrepancy from the nominal value.

All output levels are DC measurements with the power jack centre pole positive.

The units are sealed at manufacture and are not repairable.